**Forums** 

**News Archive** 

**Features** 

Resources

Marketplace

**About Us** 

# **BRAKE PARTS WAREHOUSE**

Brake pads for all occasions



#### **Side Mirror Glass Broken?**

Auto Side Mirror Glass Replacement Signal, Heated & Convex. All Makes!

Ads by Google

• R8 in Detail: Specs, Photos & Videos

• CG Visualization: An Enthusiast Builds and Audi R8

• Complete Detroit Coverage: NAIAS 2007

• <u>C6 A6 forum</u> || <u>RS 6 forum</u>

## [Thread] [Post Followup] [Post Picture] [Search Forums] [A6 / S6 (C5 Platform) Discussion]

Choose AudiWorld Discussion Forum

#### DIY Guide to 2001 Bumper Skin Removal

Posted by: Richard Solomon on 2005-10-23 20:00:28

**Account #: 525** 

A minor rear-end accident resulted in broken rear lower trim on my car. The bumper skin was a little scraped up, but not enough to be terribly concerned. The lower trim was a write-off though, half the mounts broken and the whole thing hanging down. Given that the lower trim (which wraps around the exhaust tips and has the little door for the tow hook) is about \$70, I decided to try my hand at Audi body work.

This description should be useful for anyone wanting to replace that lower trim or take their bumper skin off for repair/replacement/whatever.

### Tools needed:

10mm socket (I used both a regular and a deep socket).


T-25 TORX

Between AESIS and the fine members of Audiworld, I was able to determine the locations of the nuts to remove. There are 5ea 10mm nuts accessed through each trunk side compartment. A column of 3 to the outside, and a column of 2 just inside the trunk trim.

Even AESIS's diagrams are pretty vague, so I decided to take a series of pictures to better show the important locations.

Open the trunk and remove the two side comparment doors. Find the three outer nuts on the left side behind the CD changer mounting.

The top one:



The bottom one:



The middle & bottom ones:



The right side outer nuts are even easier:



The inner nuts are more difficult, they're jammed in between the trunk trim and the headlight assembly. I peeled back some of the sound insulation to better reach the bolts, but I still couldn't get a good picture. The best I could do was to show where the wrench sits when it's

on each nut. Once you find the first one, these really aren't too hard - just be \*CAREFUL\* not to drop a nut down into the bodywork!!! I used a 10mm deep socket here to make things a little easier.

Top left:



Bottom left:




Top right:



Bottom right:



Here's a picture of the right side after everything is off which shows the bolt holes a little better perhaps:



Now you should have 6 nuts from the outer bolts, and 4 from the inner bolts. It's time for the wheel well bolts. There are 2ea self-tapping 10mm bolts and 1ea self-tapping T-25 TORX bolt in the back of each wheel well. I had to use a box-end wrench at times here as my 17" wheels and tires made even a standard socket a tight fit.

Here's the right side, the left is simply mirrored:




Now you should have added 4ea 10mm bolts and 2ea T-25 TORX bolts to your collection. All

that's left is to unsnap the bumper skin from the guide and remove. Ok, so it took me a while to figure out the unsnapping bit. Basically you have to work the skin down and out from the wheel well, as there are a bunch of barbed plastic tabs holding the bottom of the skin in position/shape. There's probably a special Audi tool to make this easy, perhaps popsicle sticks or a plastic spatula or something would have worked - I just carefully pushed up and pulled out to work the skin off the barbs.

Here's the skin popped off on the left side:





The "magic" - this plastic guide makes everything fit beautifully even when assembled by people as clumsy as me:



Once the skin is popped off both side guides it \*should\* just slide straight back. My left top bolt got hung up on the little plastic grommet, so I spent 10-15 minutes fiddling and cursing to get it free.




Nice to see there's a real metal bumper and energy absorbers behind all that plastic:



I didn't bother taking pictures of the lower trim. Once the bumper skin is off, the 6ea T-25 bolts are obvious and simple. Re-attaching the skin is likewise straightforward. HINT: use the tape trick when putting those inner nuts back on! (Put nut in socket, wrap a layer of electrical tape around both with most tape on the socket. Once the nut is solidly threaded on, you can pull the socket and tape free.)

I did get one good laugh out of the whole deal. I've long said this is the best Italian car I've ever owned... lo and behold, what do I spy on the inside of the new lower trim piece?



Richard
'01 A6 2.7TQM
"Turbos make torque, and torque makes fun." -Corky Bell

#### Thread:

- DIY Guide to 2001 Bumper Skin Removal - Richard Solomon 2005-10-23 20:00:28 (812 views)
  - o great post. I too just got into a minor bumper accident (again), my fault....

**TeddyBGame** 2005-10-31 10:32:11 (54 views)

- \$500 painted seems like a great deal **Richard Solomon** 2005-10-31 12:28:05 (39 views)
- o "...the best Italian car I've ever owned," I like that, I'm stealin' it. IT ICONCLS 2005-10-24 09:21:21 (53 views)
  - If you think of it as a fast Japanese car, you'll be unhappy! If you think of it as Richard Solomon 2005-10-24 10:37:15 (48 views)
- o What, mine wasn't good enuf? - AudiForYou's 2.7T 2005-10-24 06:56:24 (104 views)
- o Oh, Stoney one for the FAQ! Thanks for the writeup M slatts 2005-10-23 20:53:42 (51 views)
  - Second saved this one locally. Nice work! MT Chipchase 2005-10-23 21:12:48 (49 views)

You must be registered and logged in to post. Please select an option:

Login with existing account Create a new account